

Secure Generic Sub-System (SGSS) Version 3.5

Security Policy

Product Version Details:

Part Number	Hardware Version	Software Version
1213H130	Issue 6E	3.0.0
1213R130	Issue 1	3.0.0
1213P130	Issue 2 and 2A	3.0.0

Thales e-Security
Manor Royal
Crawley
West Sussex
RH10 9HA

Tel: +44 (0)1293 580000

Fax: +44 (0)1293 589001

FIPS 140-2 Non-proprietary Security Policy

This document may be copied whole and intact including copyright notice.

Contents

1.	Glossary	1
2.	Related documents.....	1
3.	Introduction.....	2
4.	Identification and Authentication Policy.....	5
4.1	Other Security-Relevant Information	6
5.	Access Control Policy.....	7
5.1	Roles.....	7
5.2	Services	7
5.3	Cryptographic Keys and Other CSPs	7
5.4	Services that Operators are Authorised to Perform (within each Role)	8
6.	Physical Security Policy	9
6.1	Actions Required to Ensure Security is Maintained	9
7.	Error Responses	9
7.1	Power-Up Test Errors	9
7.2	Conditional Test Errors.....	9
8.	Mitigation of Other Attacks Policy	10
8.1	Movement, Temperature, Voltage and Intrusion Alarms	10
8.2	Fault Induction Attacks.....	11

1. Glossary

CA	Certificate Authority
CSP	Critical Security Parameter
ECDSA	Elliptic Curve Digital Signature Algorithm
EDC	Error Detection Code
FPGA	Field Programmable Gate Array
KAT	Known Answer Test
PIN	Personal Identification Number
RAM	Random Access Memory
SGSS	Secure Generic Sub-System
SHA-384	Secure Hashing Algorithm 384 bits

2. Related documents

FIPS140-2	Federal Information Processing Standards Publication, Security Requirements for Cryptographic Modules
FIPS180-3	Secure Hash Standard (SHS)
FIPS186-3	Digital Signature Standard (DSS)
1270A301	SGSS User Guide

3. Introduction

This document is a security policy for the Secure Generic Sub-System (SGSS), version 3.5.

The SGSS module is a multi-chip embedded cryptographic module providing functionality for the secure loading and/or upgrading of applications using the SGSS application. The SGSS is a FIPS 140-2 Security Level 3 module (Ref: FIPS140-2).

The module ensures the integrity of any application that is loaded into itself. It will only allow an application to be loaded if it has been signed by a private key that has been generated by the Certificate Authority (CA). The signature is verified using a FIPS-Approved signature verification algorithm and the public key corresponding to the private key. The Approved algorithm and the public key are securely stored in the module. This procedure ensures that only correctly signed applications can be loaded into the module.

The module implements the following FIPS-Approved algorithms:

ECDSA (Ref: FIPS186-3)

SHA-384 (Ref: FIPS180-3)

The ECDSA signature verification algorithm uses SHA-384 for its hash function.

Version 3.0 of the SGSS bootstrap application software supports the ECDSA\SHA-384 implementation. It is available in the Datacryptor Advanced Performance Plus (including the small form factor model) product and Datacryptor 2000 product.

If a new SGSS bootstrap application is loaded the replacement bootstrap application must be FIPS 140-2 validated. Only bootstrap applications were included in the FIPS 140-2 testing and validation. However loaded, applications that are FIPS 140-2 validated will run in Approved mode. The module's FIPS 140-2 validation will only be maintained if the application that is loaded by the validated bootstrap code is also FIPS 140-2 validated. The loading of non-validated application code will invalidate the module's FIPS 140-2 validation.

The SGSS uses only Approved algorithms and does not support non-Approved algorithms. Therefore the SGSS has only an Approved mode of operation.

In normal operation a user of the module need not be aware of the existence of the SGSS bootstrap. The bootstrap is restricted to configuration and maintenance tasks such as reading and updating configuration information and erasing or updating the loaded application.

When an application is present, the SGSS bootstrap will provide basic system initialisation and transfer control to the application. The application is provided with an interface to the bootstrap via the trap 15 instruction.

The module is protected by physical security provided by the SGSS tamper resistant alarm circuit and by the external module casing. The circuitry within the module is potted in a hard opaque potting material.

The following page shows the SGSS as a component of the, Datacryptor® 2000, and the

Datacryptor® Advanced Performance (including the Small Form Factor model). In each photograph the SGSS is the large black oblong case. Use of the SGSS does not imply that any product is itself FIPS 140-2 validated.



Datacryptor® 2000



Datacryptor® Advanced Performance Small Form Factor



Datacryptor® Advanced Performance

4. Identification and Authentication Policy

There are two roles associated with the module. These are the crypto-officer role and the user role. There is no maintenance role associated with the module.

The crypto-officer role involves the loading of a public key certificate into the module at the factory. The public key certificate is used by the module to verify the signature on any application that it loads.

An authorised crypto-officer performs the loading of the public key certificate at the factory.

Once the module is fielded, new applications may be generated at the plant and signed using the private key that is held securely at the factory. (Security at the factory is provided by procedural controls.) In the field the user, acting on behalf of the factory, may load the signed application into the module where the signature is verified using the public key certificate. This is the only cryptographic application offered by the module's software. Details on how to perform the user role securely are contained in the document SGSS User Guide (Ref: 1270A301).

Authentication of the crypto-officer is provided by secure manufacturing procedures at the factory.

The authentication data required of the user is the correctly signed application code. This means that the user's authentication data is effectively the private component of the CA key pair. The authentication data contained in the module will be the corresponding public key and signature algorithm.

The only identity associated with the module is that of the factory. The crypto-officer, acting on behalf of the factory, initialises the module by inserting the public key certificate into the module. The user, also acting on behalf of the factory, loads a signed application in the field. The signature on the application therefore identifies and authenticates the factory.

The corresponding strength of the authentication mechanism depends on the size of the private key space associated with the FIPS-Approved algorithm (ECDSA using SHA-384) used for generating and verifying the digital signatures. Since the module uses only these FIPS-Approved algorithms (see <http://csrc.nist.gov/cryptval/>) the size of the key space provides an extremely high level of security for the authentication mechanism. This is shown by the following mathematical arguments for ECDSA.

Let x be the size of a private key space used in ECDSA. Then $x > 2^{192} > 1000000$, so that $1/x < 1/1000000$. It follows that

- the probability that a random attempt to use the authentication mechanism will succeed or that a false acceptance will occur is (significantly) less than one in 1,000,000
- the probability that multiple attempts to use the authentication mechanism during a one-minute period will succeed or that a false acceptance will occur is (significantly) less than one in 100,000. It typically takes 35 seconds for each attempt to use the authentication mechanism – only available via the relatively slow serial interface.

4.1 Other Security-Relevant Information

FIPS Approved Mode of Operation

The SGSS only has an Approved mode of operation. The following conditions must be satisfied to achieve the FIPS 140-2 Level 3 Approved mode.

FIPS 140-2 Approved security methods are used

The following method must be used:

- ECDSA/SHA-384 (FIPS Certificates #283/1717)

5. Access Control Policy

5.1 Roles

As already discussed the module supports a crypto-officer and a user role. There is no maintenance role associated with the module.

5.2 Services

The only cryptographic service provided by the module is the loading of signed applications. The user will be able to load an application into the module provided that the application is properly signed and there is sufficient memory space in the SGSS to store the loaded application.

Unauthenticated users may perform the following non-sensitive services:

- Echo (Echoes back an input string)
- Erase application (Erases application)
- Get version (Provides SGSS version number)
- Get CA name (Provides name of CA (factory) which generated public/private key pair)
- Read/Write application configuration (Provides/selects current configuration)
- Reboot unit (Resets the module)
- Set comms baud rate (Sets the communication rate)
- Get date/time (from the real-time clock)
- Read/write to/from unused FLASH (for storage of semi-permanent application data)
- Get CA (read CA properties)

The self-test services provided by the module are an Error Detection Code (EDC) test for validating the bootstrap application, and known answer tests (KATs) on the signature verification algorithms (ECDSA). Self-tests are performed at start-up and after a service request to reboot the unit.

5.3 Cryptographic Keys and Other CSPs

The only cryptographic key directly employed by the module is the public key component of the CA key pair. This is stored in the flash in the SGSS in plaintext form and is protected by the physical security mechanisms associated with the SGSS. This CA public key never leaves the SGSS. Disclosure of the CA public key does not constitute a security risk for the module since possession of the public key would not enable an attacker to sign applications and thereby enter them into the module.

CA private keys are not directly employed by the module. They are used to sign an application that is to be loaded into the module. CA private keys are never loaded into the module and are stored securely with the manufacturer's factory.

There are no passwords or PINs associated with the operation of the module.

The only other security-relevant data are the Approved signature algorithms used by the module.

These algorithms are publicly available and their disclosure would constitute no threat.

5.4 Services that Operators are Authorised to Perform (within each Role)

The crypto-officer is authorised to load the public key certificate into the module at the factory.

The user is authorised to perform the application-loading service provided by the module.

The user will have access to the signed application that is to be loaded into the module. Procedures should be implemented to ensure that only authorised users are allowed to access the signed application. However the user will not have direct access to the particular CA private key that has been used to sign the application. This means that the user would not be able to sign another application and load it into the module. The signing of the application must be performed by the vendor or by the developer of the application.

The user is also authorised to perform other services provided by the module (see Section 5.2 above).

6. Physical Security Policy

6.1 Actions Required to Ensure Security is Maintained

The SGSS is a tamper-resistant multiple-chip embedded cryptographic module consisting of production grade components intended to meet FIPS 140-2 Level 3. It does not support a maintenance role and therefore security concerns arising from such a role are not relevant.

The SGSS is potted with a hard epoxy resin that is opaque within the visible spectrum. The potted module is contained in a hard, solid copper shell. These components provide the module's tamper evidence. The components should be inspected for evidence of tamper. The physical security mechanism described above uses passive techniques and therefore no testing of the mechanism is required.

7. Error Responses

7.1 Power-Up Test Errors

At power-up the SGSS automatically validates the integrity of its application using an EDC algorithm. If the integrity of the application is validated then the SGSS performs a known answer test (KAT) on the signature verification algorithm (ECDSA).

If the EDC test or either of the KAT tests fails, an error message is logged and then the module reboots itself.

7.2 Conditional Test Errors

When a signed application is loaded then the signature on the application is checked using the signature verification algorithm (ECDSA). If the verification fails then the application is not loaded into the unit and the SGSS outputs an error message to indicate that the signature verification was unsuccessful.

8. Mitigation of Other Attacks Policy

8.1 Movement, Temperature, Voltage and Intrusion Alarms

The module contains a tamper resistant intrusion detection system that surrounds the secure area. This intrusion detection system is an input to the alarm circuit and cannot be disabled.

The physical security provided by the SGSS operates as a protection mechanism for the RAM, FPGA and Coldfire processor. When there is only a bootstrap present the intrusion detection system serves no useful function. However if a certified application is loaded in the module then the RAM and FPGA are used to contain critical security parameters and as such require protection. The alarm circuit protects the contents of the RAM and cipher FPGA by erasing them if an attempt is made to access the secure area. The contents of the flash are not erased when the alarm is triggered and consequently no sensitive information is stored in flash.

The intrusion detection system consists of two circuits: a continuity circuit and a guard circuit. These two circuits are wrapped around the secure area and then potted in a hard opaque resin.

The alarm is triggered if the continuity circuit is broken or if the two circuits are bridged. Any attempt to access the secure area by cutting or drilling would result in the alarm circuit being triggered by either breaking the continuity circuit or bridging the two circuits. The circuits are bonded to the resin so that any attempt to gain access by forcibly removing the resin will break the continuity circuit and hence trigger the alarm. Any attempt to dissolve the resin will damage the circuits and trigger the alarm.

The alarm circuit is powered from the main power supply when this is available, but if the module is not powered up then it is powered by a battery. The battery is mounted outside the SGSS. If the battery is disconnected or fails the alarm triggers. This ensures that the module's tamper response and zeroization circuitry is operational at all times.

In addition to the alarm circuit the SGSS has a sensor that detects movement. Any abnormal movement of the module will trigger the motion alarm.

As well as providing tamper resistance the SGSS incorporates environmental failure protection features enabling the module to monitor and respond to fluctuations in the operating temperature and voltage. If the temperature moves outside a predetermined range (-5°C to 60°C) a temperature sensor causes the alarm to be triggered. Similarly if the voltage on the +5v rail surges or is actively driven above the normal level then the alarm is triggered, and if the voltage drops below the normal level then the module shuts down.

In addition to zeroizing all CSPs the effect of triggering the alarm is that the supply rails to the RAM, the cipher FPGA and the ColdFire microprocessor are clamped to ground. This process is much faster than simply removing power from the devices. Additionally the interface lines are disconnected.

If the alarm condition is temporary then the unit will reset itself following removal of the alarm condition. For example if the alarm is triggered by a rise in temperature then the unit will reset

itself after the temperature falls.

In some circumstances the triggering of the alarm will be permanent, i.e. the unit will not be able to reset itself due to the persistence of the alarm condition. This would happen, for example, if the alarm circuit were triggered by an intrusion attack. In this case the unit must be returned to the factory for the alarm to be reset.

Both the movement alarm and the temperature alarm can be turned on or off. Before an application has been loaded (i.e. when only the bootstrap application is present) the temperature alarm is enabled and the motion alarm is disabled. The other alarms (i.e. the intrusion detection system and the voltage alarm) are permanently enabled.

The movement alarm and the temperature alarm were not tested as part of the FIPS 140-2 Level 3 validation.

After the security settings have been decided upon (e.g. whether to enable or disable the motion sensor) the physical security mechanisms provided by the SGSS will not require any action on the part of the operator: the module is designed for use in an insecure domain. An attempt to breach security will result in automatic disabling of the module's functionality.

When the module has been loaded with an application it will be necessary to ensure that it is subject to appropriate protection against unauthorised use. However such protection measures would form part of the security policy for the loaded application rather than the module itself and are therefore outside the scope of a security policy for the module.

8.2 Fault Induction Attacks

Fault induction attacks make use of fluctuations in external forces to cause processing errors within a module.

The module provides protection against certain types of fault induction attack. The module contains a temperature sensor and a mechanism to detect abnormal voltage variations.

The temperature sensor can be enabled or disabled by the user. The user must enable the temperature alarm in order to provide constant protection against a fault induction attack utilising temperature extremes.

The temperature sensor (if enabled) and the outside range voltage sensor will not require any further action on the part of the operator. If either of these alarms is triggered then the module's functionality will be automatically disabled.

There are no conditions under which the temperature and abnormal voltage mechanisms are known to be ineffective.